

WB12y-DTB



Max.Loading capacity 1,200kg

Machine Size			Engine		
Overall Length	mm	2,560	Туре	-	Liquid-cooled Diesel/Kubota Z602
Overall Width	mm	975	Output/Rotation	PS/rpm	10.8
Overall Height	mm	2,115	Displacement	сс	599
Ground Clearance	mm	165	Starting method	-	Cell
Machine Weight	kg	915	Fuel Tank Capacity	L	19.5
Crawler			Bucket Type		
Crawler Centre	mm	720	Bucket Type	-	180°
Ground Contact	mm	1,180	Floor Height	mm	600
Width	mm	230	Overall Length	mm	1,400
Travel			Overall Width	mm	880
Operating	-	Wet Multi-plate	Overall Height	mm	470
Transmission	-	Continuously Variable Transmission	Max. Loading Capacity	kg	1,200
Speed			Deck Body Capacity	m³	0.37
Forward	km/h	0~5.6	Dumping Angle	۰	80
Reverse	km/h	0~3.5			



Website: http://winbull.co.jp/

Head Office (Factory, Trading Division, Domestic Sales Division):

399 Tojitsu, Kato-shi, Hyogo Pref., Japan, 673-1434

Kobe Office (Overseas Division):

Park Court Motomachi WEST 5F,

6-1-4 Motomachidori, Chuo-ku, Kobe, Hyogo Pref., Japan, 650-0022

What's Special?



ull open engine cover Easy maintenance by setting engine under the seat.

/14.7PS.



Overal widt 975mm Works great in narrow places and on rough




ngine Kubota Z602 engine. Engine Spec 10.8kw



Can drive easily to forward & reverse by HST without switching

Travelling Performance


The truck roller balance helps body stability & high turn performance.




WB12 γ −DTB



WINBULL_YAMAGUCHI_KOBE





Contact Us





WINBULL YAMAGUCHI CORPORATION Park Court Motomachi WEST 5F. Website: http://winbull.co.jp/

Head Office (Factory, Trading Division, Domestic Sales Division): 399 Tojitsu, Kato-shi, Hyogo Pref., Japan, 673-1434

Kobe Office (Overseas Division):

6-1-4 Motomachidori, Chuo-ku, Kobe, Hyogo Pref., Japan, 650-0022